

## TECHNICAL DATA

- Single high output
- 100% Duty Cycle
- Variable fog output
- Last operation mode memory
- Recordable failure / anomaly logs
- Firmware upgradable
- Automatic Purging System™ (APS™)
- Maximum gas pressure input: 4.14 Bar (60 psi)
- 3 standard USITT DMX512 channels, XLR-5
- RDM compliant
- Second personality, MAX 3000 configuration setting
- USB 2.0 Link connector (control)

### Me1

Maximum fog output (per minute)	100 m <sup>3</sup> (3,531 ft <sup>3</sup> )
Fluid consumption (per hour at 2.76 bar/40 psi)	1 L (34 oz / 0.26 US gallon)
Gas type	CO <sub>2</sub> or N <sub>2</sub>
Gas consumption (per hour at 2.76 bar/40 psi)	1 kg (2.2 lb)
Control	4-button LCD user interface, 3 standard USITT DMX512 channels, XLR-5 connectors, RDM compliant
Reservoir capacity	2,5 L (0.66 US gallon)
Automatic Purging System (APS)	Standard feature
Fog colour	Pure white
Particle size	0,5 - 0,7 micron
Warm-up time (maximum)	8 minutes
Fluid type (S.D.S. available on request)	MDG Neutral Fluid
Operating voltage	100-250 VAC, 50/60 Hz single phase
Power consumption	715 W
Dimension	Length 61 cm (24") Width 18 cm (7") Height 30 cm (12")
Weight	16 kg (35 lb)
Shipping weight (without flight case)	20 kg (44 lb)
Shipping weight (with flight case)	29 kg (64 lb)
Approval	CE, CSA and UL

## FLUID

### MDG Neutral Fluid

Safe, non-toxic, with the longest hanging time in the industry.

Available in:

4 L (1 US gallon),  
20 L (5.3 US gallon),  
200 L (53 US gallon) and  
1000 L (264 US gallon).



## ACCESSORIES

### Flight case

Durable for safe and easy transport



Creating better fog since 1980

10301 av. Pelletier, Montréal, Québec, Canada H1H 3R2  
T (514) 272-6040 1-800-663-3020 F (514) 722-3229  
info@mdgfog.com www.mdgfog.com